



NOTES:

1. TORQUE RATINGS, Nm
SYMMETRIC TORQUE: 4.5, CW=CCW
2. CYCLE LIFE:
WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN
±25% OF TORQUE SPECIFICATION.
3. FINISH: PLATING
4. 360 DEGREE SHAFT ROTATION
5. U.S. PAT. NO. 9,609,770

METRIC(MM)	[ENGLISH] (IN)	LEEEO			DWG NO.								
0-3 ± 0.15	0-0.118 ± 0.006							BH12-1003-45					
3-10 ± 0.20	0.118-0.394 ± 0.008							TITLE					
10-30 ± 0.25	0.394-1.181 ± 0.010							BH12					
30-50 ± 0.30	1.181-2.000 ± 0.012							MATERIAL					
50-100 ± 0.40	2.000-4.000 ± 0.016										STEEL		
100-200 ± 0.50	4.000-8.000 ± 0.020							REV					
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION					APPROVED JLIU		DRAWN BCHEN				SHEET 1 OF 1		SCALE: 2.000