



NOTES:

1. TORQUE RATINGS, Nm
SYMMETRIC TORQUE: 0.13, CW=CCW
2. CYCLE LIFE:
WITHIN 10,000 CYCLES STATIC TORQUE STAY WITHIN
±35% OF TORQUE SPECIFICATION.
3. FINISH: PLATING
4. 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	LEEEO			DWG NO.			
0-3 < ±0.15	0-0.118 < ±0.006				BH4-1003-01			
3-10 < ±0.20	0.118-0.394 < ±0.008	TITLE			BH4			
10-30 < ±0.25	0.394-1.181 < ±0.010	APPROVED	DRAWN		MATERIAL			
30-50 < ±0.30	1.181-2.000 < ±0.012	JLIU	BCHEN		STEEL			
50-100 < ±0.40	2.000-4.000 < ±0.016	SHEET 1 OF 1			SCALE: 4.000	REV	A3	☉ □
100-200 < ±0.50	4.000-8.000 < ±0.020				PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION			