



NOTES:

1. TORQUE RATINGS,

PART NUMBER	SYMMETRIC TORQUE - Nm
BH8-1003-05	0.5
BH8-1003-08	0.8

2. CYCLE LIFE:
WITHIN 10,000 CYCLES STATIC TORQUE STAY WITHIN
±25% OF TORQUE SPECIFICATION.

3. FINISH: PLATING

4. 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	LEEEO			DWG NO.			
0-3 ± 0.15 3-10 ± 0.20 10-30 ± 0.25 30-50 ± 0.30 50-100 ± 0.40 100-200 ± 0.50	0-0.118 ± 0.006 0.118-0.394 ± 0.008 0.394-1.181 ± 0.010 1.181-2.000 ± 0.012 2.000-4.000 ± 0.016 4.000-8.000 ± 0.020				BH8-1003-xx			TITLE
<small>PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION</small>			BH8					MATERIAL
			APPROVED	DRAWN				STEEL
JLIU	BCHEN	REV						
SHEET 1 OF 1		SCALE: 2.000		A3				