



NOTES:

1. TORQUE RATINGS, Nm (LB-IN) :
 SYMMETRIC TORQUE: 0.1-0.9 (0.9-8.0), CW=CCW
 ASYMMETRIC TORQUE: 0.2-1.1 (1.8-9.7)-HIGH TORQUE
 **LOW TORQUE IS ABOUT 65% OF HIGH TORQUE
 **STATIC TORQUE COULD BE SPECIFIED AT EVERY 0.01Nm (0.1LB-IN) INTERVAL WITHIN RANGE GIVEN ABOVE
2. CYCLE LIFE:
 WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN ±20% OF TORQUE SPECIFICATION.
3. FINISH:
 A. NATURE
 B. BLACK OXIDE
4. 360 DEGREE SHAFT ROTATION
5. CUSTOM MOUNTING HOLE DISTANCE FROM 7.8MM TO 13.25MM

METRIC(MM)	[ENGLISH] (IN)
0-3 ± 0.15	0-0.118 ± 0.006
3-10 ± 0.20	0.118-0.394 ± 0.008
10-30 ± 0.25	0.394-1.181 ± 0.010
30-50 ± 0.30	1.181-2.000 ± 0.012
50-100 ± 0.40	2.000-4.000 ± 0.016
100-200 ± 0.50	4.000-8.000 ± 0.020

PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION

LEEEO

APPROVED	DRAWN
JLIU	BCHEN

SHEET 1 OF 1 SCALE: 1.000

DWG NO. QM-0700 TYPEC	
TITLE QM7C	
MATERIAL ZINC ALLOY AND STEEL	
REV	A3