



NOTES:

- TORQUE RATINGS, Nm
 SYMMETRIC TORQUE(TILT): 2.0, CW=CCW
 SYMMETRIC TORQUE(SWIVEL): 1.0, CW=CCW
- CYCLE LIFE:
 WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN
 ±25% OF TORQUE SPECIFICATION.
- FINISH: PLATING
- 360 DEGREE SHAFT ROTATION

METRIC	(ENGLISH)	LEEEO		DWG NO.	
0-3 ± 0.15	0-0.118 ± 0.004			TS10-1003-10	
3-10 ± 0.20	0.118-0.394 ± 0.005	TITLE			
10-30 ± 0.25	0.394-1.181 ± 0.010	TS10			
30-50 ± 0.30	1.181-2.000 ± 0.012	APPROVED	DRAWN	MATERIAL	
50-100 ± 0.40	2.000-4.000 ± 0.016	JLIU	BCHEN	STEEL	
100-200 ± 0.50	4.000-8.000 ± 0.020	SHEET 1 OF 1		SCALE: 2.000	
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION		REV		A3	

