



NOTES:

1. TORQUE RATINGS, Nm :

PART NUMBER	SYMMETRIC TORQUE
BH10S-1003-05	0.5
BH10S-1003-10	1.0
BH10S-1003-20	2.0

2. CYCLE LIFE:
WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN
±25% OF TORQUE SPECIFICATION.

3. FINISH: PASSIVATION TREATMENT

4. OIL RING SEALS FOR PROTECTION AGAINST
ENVIRONMENT CONTAMINATION

5. 360 DEGREE SHAFT ROTATION

6. U.S. PAT. NO. 9,609,770

METRIC(MM)	[ENGLISH] (IN)	LEEEO		DWG NO.		
0-3 < ±0.15	0-0.118 < ±0.006			BH10S-1003-xx		
3-10 < ±0.20	0.118-0.394 < ±0.008	TITLE			BH10S	
10-30 < ±0.25	0.394-1.181 < ±0.010	MATERIAL				STAINLESS STEEL 316
30-50 < ±0.30	1.181-2.000 < ±0.012	APPROVED	DRAWN	REV		
50-100 < ±0.40	2.000-4.000 < ±0.016	JLIU	BCHEN	A3		
100-200 < ±0.50	4.000-8.000 < ±0.020	PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION		SCALE: 2.000		
		SHEET 1 OF 1				