



NOTES:

- TORQUE RATINGS, Nm  
SYMMETRIC TORQUE: 0.5, CW=CCW
- CYCLE LIFE:  
WITHIN 10,000 CYCLES STATIC TORQUE STAY WITHIN  
±25% OF TORQUE SPECIFICATION.
- FINISH: PLATING
- 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	<b>LEEEO</b>		DWG NO.	
0-3 < ±0.15	0-0.118 < ±0.006			BH6-1003-05	
3-10 < ±0.20	0.118-0.394 < ±0.008	TITLE			
10-30 < ±0.25	0.394-1.181 < ±0.010	BH6			
30-50 < ±0.30	1.181-2.000 < ±0.012	APPROVED	DRAWN	MATERIAL	
50-100 < ±0.40	2.000-4.000 < ±0.016	JLIU	BCHEN	STEEL	
100-200 < ±0.50	4.000-8.000 < ±0.020			REV	A3
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION		SHEET 1 OF 1		SCALE: 3.000	