



NOTES:

1. TORQUE RATINGS, Nm  
SYMMETRIC TORQUE: 0.8, CW=CCW
2. CYCLE LIFE:  
WITHIN 10,000 CYCLES STATIC TORQUE STAY WITHIN  
±25% OF TORQUE SPECIFICATION.
3. FINISH: PLATING
4. 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	<b>LEEEO</b>			DWG NO.		
0-3 < ±0.15	0-0.118 < ±0.006				BH8-1003-08		
3-10 < ±0.20	0.118-0.394 < ±0.008	TITLE			BH8		
10-30 < ±0.25	0.394-1.181 < ±0.010	APPROVED	DRAWN		MATERIAL		
30-50 < ±0.30	1.181-2.000 < ±0.012	JLIU	BCHEN		STEEL		
50-100 < ±0.40	2.000-4.000 < ±0.016	PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION			REV	A3	☉ □
100-200 < ±0.50	4.000-8.000 < ±0.020				SHEET 1 OF 1	SCALE: 2.000	