



NOTES:

1. TORQUE RATINGS, Nm
SYMMETRIC TORQUE: 0.6, CW=CCW
2. CYCLE LIFE:
WITHIN 10,000 CYCLES STATIC TORQUE STAY WITHIN
±25% OF TORQUE SPECIFICATION.
3. FINISH: PLATING
4. 360 DEGREE SHAFT ROTATION

METRIC(MM)	[ENGLISH] (IN)	LEECO		DWG NO.		
0-3 < ±0.15	0-0.118 < ±0.006			BH7-1003-06		
3-10 < ±0.20	0.118-0.394 < ±0.008	APPROVED		DRAWN		TITLE
10-30 < ±0.25	0.394-1.181 < ±0.010					BH7
30-50 < ±0.30	1.181-2.000 < ±0.012	JLIU		BCHEN		MATERIAL
50-100 < ±0.40	2.000-4.000 < ±0.016					STEEL
100-200 < ±0.50	4.000-8.000 < ±0.020	SHEET 1 OF 1		SCALE: 3.000		REV
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEECO TECHNOLOGIES CORPORATION						A3