



NOTES:

1. TORQUE RATINGS, Nm :

PART NUMBER	SYMMETRIC TORQUE
SH10L-1055-10	1.0
SH10L-1055-20	2.0
SH10L-1055-30	3.0
SH10L-1055-40	4.0
SH10L-1055-50	5.0

- CYCLE LIFE:
WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN ±25% OF TORQUE SPECIFICATION.
- FINISH: PLATING AND NATURE
- 360 DEGREE SHAFT ROTATION
- U.S. PAT. NO. 9,609,770

METRIC(MM)	[ENGLISH] (IN)	LEEEO		DWG NO.		
0-3 < ±0.15	0-0.118 < ±0.006			SH10L-1055-xx		
3-10 < ±0.20	0.118-0.394 < ±0.008	APPROVED		DRAWN		TITLE
10-30 < ±0.25	0.394-1.181 < ±0.010					SH10L
30-50 < ±0.30	1.181-2.000 < ±0.012	JLIU		BCHEN		MATERIAL
50-100 < ±0.40	2.000-4.000 < ±0.016					STEEL
100-200 < ±0.50	4.000-8.000 < ±0.020	SHEET 1 OF 1		SCALE: 1.800	REV	A3
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION						