



NOTES:

1. TORQUE RATINGS, Nm :

PART NUMBER	SYMMETRIC TORQUE
QM15-1076-23	2.3
QM15-1076-34	3.4
QM15-1076-42	4.2
QM15-1076-51	5.1

PART NUMBER	ASYMMETRIC CW TORQUE	ASYMMETRIC CCW TORQUE
QM15-2076-34	3.4	2.3
QM15-2076-42	4.2	2.8
QM15-2076-51	5.1	3.5
QM15-2076-61	6.1	4.1
QM15-3076-34	2.3	3.4
QM15-3076-42	2.8	4.2
QM15-3076-51	3.5	5.1
QM15-3076-61	4.1	6.1

2. CYCLE LIFE:

WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN ±20% OF TORQUE SPECIFICATION.

3. FINISH:

- A. NATURE
- B. BLACK PAINT

4. 270 DEGREE SHAFT ROTATION

5. OIL RING SEALS FOR PROTECTION AGAINST ENVIRONMENT CONTAMINATION

METRIC(MM)	[ENGLISH] (IN)	<b>LEEEO</b>		DWG NO.		
0-3 < ±0.15	0-0.118 < ±0.006			QM15-x076-xx		
3-10 < ±0.20	0.118-0.394 < ±0.008	TITLE		QM15		
10-30 < ±0.25	0.394-1.181 < ±0.010			MATERIAL		STEEL&ZINC
30-50 < ±0.30	1.181-2.000 < ±0.012	APPROVED	DRAWN	REV		
50-100 < ±0.40	2.000-4.000 < ±0.016	JLIU	BCHEN			
100-200 < ±0.50	4.000-8.000 < ±0.020	SHEET 1 OF 1		SCALE: 1.500		
PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION						