



NOTES:

1. TORQUE RATINGS, Nm :

PART NUMBER	SYMMETRIC TORQUE
CT10A-1025-09	0.9
CT10A-1025-14	1.4
CT10A-1025-18	1.8
CT10A-1025-23	2.3
CT10A-1025-27	2.7

PART NUMBER	ASYMMETRIC CW TORQUE	ASYMMETRIC CCW TORQUE
CT10A-2025-14	1.4	0.9
CT10A-2025-18	1.8	1.2
CT10A-2025-23	2.3	1.5
CT10A-2025-27	2.7	1.8
CT10A-2025-34	3.4	2.3
CT10A-3025-14	0.9	1.4
CT10A-3025-18	1.2	1.8
CT10A-3025-23	1.5	2.3
CT10A-3025-27	1.8	2.7
CT10A-3025-34	2.3	3.4

2. CYCLE LIFE:  
WITHIN 25,000 CYCLES STATIC TORQUE STAY WITHIN ±20% OF TORQUE SPECIFICATION.
3. FINISH: NATURE
4. 360 DEGREE SHAFT ROTATION

<b>METRIC(MM)</b> 0-3< ±0.15 3-10< ±0.20 10-30< ±0.25 30-50< ±0.30 50-100< ±0.40 100-200< ±0.50	<b>[ENGLISH] (IN)</b> 0-0.118<±0.006 0.118-0.394<±0.008 0.394-1.181<±0.010 1.181-2.000<±0.012 2.000-4.000<±0.016 4.000-8.000<±0.020	<h1 style="text-align: center;">LEEEO</h1>		<b>DWG NO.</b> CT10A-x025-xx	
				<b>TITLE</b> CT10A	
<b>PROPRIETY ITEM - ALL INFORMATION DISCLOSED HEREON IS CONFIDENTIAL AND ALL RIGHTS PATENT AND OTHERWISE ARE RESERVED BY LEEEO TECHNOLOGIES CORPORATION</b>		<b>APPROVED</b> JLIU	<b>DRAWN</b> BCHEN	<b>MATERIAL</b> STEEL & ZINC	
		<b>SHEET 1 OF 1</b>		<b>SCALE: 2.500</b>	<b>REV</b> A3